

The pstool package

Concept by Zebb Prime
Package by Will Robertson*

v1.5e 2018/01/20

Abstract

This package defines the `\psfragfig` user command for including EPS files that use `psfrag` features in a pdf \LaTeX document. The command `\pstool` can be used to define other commands with similar behaviour.

Contents

I	USER DOCUMENTATION	1	II	IMPLEMENTATION	10
1	Introduction	1	6	Package information	10
2	Getting started	2	7	Code	10
3	User commands	2	8	Macros	14
4	Package options	4	9	Command parsing	18
5	Miscellaneous details	7	10	User commands	20
			11	The figure processing	21
			12	User commands	26

Part I

User documentation

1 Introduction

While directly producing PDF output with pdf \LaTeX is a great improvement in many ways over the ‘old method’ of $\text{DVI} \rightarrow \text{PS} \rightarrow \text{PDF}$, it loses the ability to interface with a generic PostScript workflow, used to great effect in numerous packages, most notably PSTricks and `psfrag`.

*wspr81@gmail.com

Until now, the best way to use these packages while running pdfL^AT_EX has been to use the pst-pdf package, which processes the entire document through a filter, sending the relevant PostScript environments (only) through a single pass of L^AT_EX producing DVI→PS→PDF. The resulting PDF versions of each graphic are then included into the pdfL^AT_EX document in a subsequent compilation. The auto-pst-pdf package provides a wrapper to perform all of this automatically.

The disadvantage with this method is that for every document compilation, *every* graphic must be re-processed. The pstool package uses a different approach to allow each graphic to be processed only as needed, speeding up and simplifying the typesetting of the main document.

At present this package is designed solely as a replacement for pst-pdf in the rôle of supporting the psfrag package (which it loads) in pdfL^AT_EX.

More flexible usage to provide a complete replacement for pst-pdf (e.g., supporting the `\begin{postscript}` environment) is not planned at this stage. If you simply need to automatically convert plain EPS files to PDF, I recommend using the epstopdf package with the `[update,prepend]` package options (epstopdf and pstool are compatible, but **only** if epstopdf is loaded first).

2 Getting started

Processing pdfL^AT_EX documents with pstool requires the ‘shell escape’ feature of pdfT_EX to be activated. This allows execution of auxiliary commands from within L^AT_EX, a feature which is often disabled by default for security reasons. If shell escape is not enabled, a warning will be issued in console output when the package is loaded. Depending how you compile your L^AT_EX document, shell escape is enabled in different ways.¹

Load the package as usual; no package options are required by default, but there are a few useful options described later in section 4. Note that you do not need to load psfrag separately. You also do not need to load graphicx separately, but if you do so, ensure that you do *not* include driver information (such as `[pdftex]`); this will play havoc with pstool’s automatic processing stage.

3 User commands

The low-level generic command provided by this package is

```
\pstool <suffix> [<options>] {<filename>} {<input definitions>}
```

It converts the graphic `<filename>.eps` to `<filename>.pdf` with psfrag macros in `<filename>.tex` through a unique DVI→PS→PDF process for each graphic, using

¹On the command line, use the `-shell-escape` switch. Otherwise, you’re on your own.

the preamble of the main document. The resulting graphic is then inserted into the document, with $\langle options \rangle$ consisting of options for `graphicx` (e.g., `angle`, `scale`) or for `pstool` (as described later in Section 4). Note that these optional arguments take effect in the *processing stage*; if you change the $\langle options \rangle$, you must manually re-process the figure. The third argument to `\pstool` allows arbitrary $\langle input definitions \rangle$ (such as `\psfrag` directives) to be inserted before the figure as it is processed.

By default, `\pstool` processes the graphic $\langle filename \rangle$.eps if $\langle filename \rangle$.pdf does not already exist, or if the EPS file is *newer* than the PDF. Additionally, if one or more macro files are associated with the graphic, they are also checked whether they have changed since the PDF was generated. The macro file(s) can be defined per-graphic as for the `\psfragfig` command (see below), and/or globally as for the `[macro-file=...]` package option described in Section 4.1.

The `\pstool` command can take an optional `*` or `!` suffix to change its behaviour:

`\pstool*` Always process the figure;
`\pstool!` Never process the figure.

The behaviour in all three cases can be overridden globally by the package option `[process]` as described in section 4.2.

3.1 The main `\psfragfig` command

It is useful to define higher-level commands based on `\pstool` for including specific types of EPS graphics that take advantage of `psfrag`. The `pstool` package defines the following wrapper command `\psfragfig`, which also supports the `*` or `!` suffixes described above.

`\psfragfig` $\langle suffix \rangle$ [$\langle opts \rangle$] { $\langle filename \rangle$ }

This catch-all macro is designed to support a wide range of graphics naming schemes. It inserts an EPS file named either $\langle filename \rangle$ -psfrag.eps or $\langle filename \rangle$.eps (in that order of preference), and uses `psfrag` definitions contained within either $\langle filename \rangle$ -psfrag.tex or $\langle filename \rangle$.tex. The `\psfragfig` command can be used to insert figures produced by the `MATHEMATICA` package `MathPSfrag` or the `MATLAB` package `matlabfrag`. `\psfragfig` also accepts an optional braced argument:

`\psfragfig` $\langle suffix \rangle$ [$\langle opts \rangle$] { $\langle filename \rangle$ } { $\langle input definitions \rangle$ }

The command behaves as above, but also inserts the arbitrary code $\langle input definitions \rangle$ into the processing stage; this additional code will usually be used to define new or override existing `psfrag` commands.

4 Package options

Package options can be set or overridden at any time with `\pstoolsetup{<pstool settings>}`. As mentioned in the previous section, these options also may be set in the optional argument to `\pstool` and `\psfragfig`, in which case they apply to that figure alone.

4.1 Macro file(s)

As mentioned above, macro files can be used to store commands for processing `psfrag` graphics. If they change, these macro files can trigger a pre-compilation of the graphics. While usually the macro files will be defined per-graphic (such as `foo.eps` having a `foo-psfrag.tex` file), `pstool` will also load a ‘master’ macro file for each graphic if it exists using the `[macro-file=...]` option.

The default is `[macro-file=<jobname>-pstool.tex]`; if this file does not exist then no macro file is loaded. That is, if your document is called `thesis.tex`, the master macro file will be loaded in each graphic as `thesis-pstool.tex`, if it exists.

This option is useful if you have macro definitions in a single file that are used by multiple graphics. By updating the definitions file, the graphics in the document will be automatically updated. (Note that this file can contain plain \LaTeX definitions; the `\psfrag` commands can still be located in the per-graphic `.tex` files.)

To suppress the loading of a master macro file in all cases, use an empty argument for the package option, as in `[macro-file={}]`.

4.2 Forcing/disabling graphics processing

While the suffixes `*` and `!` can be used to force or disable (respectively) the processing of each individual graphic, sometimes we want to do this on a global level. The following package options override *all* `pstool` macros:

[process=auto] This is the default mode as described in the previous section, in which graphics without suffixes are only (re-)processed if the `EPS` file is newer or the `PDF` file does not exist;

[process=all] Suffixes are ignored and all `\pstool` graphics are processed;

[process=none] Suffixes are ignored and no `\pstool` graphics are processed.²

²If `pstool` is loaded in a \LaTeX document in `DVI` mode, this is the option that is used since no external processing is required for these graphics.

4.3 Cropping graphics

The default option `[crop=preview]` selects the preview package to crop graphics to the appropriate size for each auxiliary process.

However, when an inserted label protrudes from the natural bounding box of the figure, or when the original bounding box of the figure is wrong, the preview package will not always produce a good result (with parts of the graphic trimmed off the edge). A robust method to solve this problem is to use the `pdfcrop` program instead.³ This can be activated in `pstool` with the `[crop=pdfcrop]` package option.

4.4 Temporary files & cleanup

Each figure that is processed spawns an auxiliary \LaTeX compilation through $\text{DVI} \rightarrow \text{PS} \rightarrow \text{PDF}$. This process is named after the name of the figure with an appended string suffix; the default is `[suffix={-pstool}]`. Most of these suffixed files are “temporary” in that they may be deleted once they are no longer needed.

As an example, if the figure is called `ex.eps`, the files that are created are `ex-pstool.tex`, `ex-pstool.dvi`, `...`. The `[cleanup]` package option declares via a list of filename suffixes which temporary files are to be deleted after processing.

The default is `[cleanup={.tex, .dvi, .ps, .pdf, .log}]`. To delete none of the temporary files, choose `[cleanup={}]` (useful for debugging). Note that if you want cross-referencing to work correctly for labels in figures, etc., then you must not delete the `.aux` file (see Section 5.3).

4.5 Interaction mode of the auxiliary processes

Each graphic echoes the output of its auxiliary process to the console window; unless you are trying to debug errors there is little interest in seeing this information. The behaviour of these auxiliary processes are governed globally by the `[mode]` package option, which takes the following parameters:

`[mode=batch]` hide almost all of the \LaTeX output (*default*);

`[mode=nonstop]` echo all \LaTeX output but continues right past any errors; and

`[mode=errorstop]` prompt for user input when errors are encountered.

These three package options correspond to the \LaTeX command line options `-interaction=batchmode`, `=nonstopmode`, and `=errorstopmode`, respectively. When `[mode=batch]` is activated, then `dvips` is also run in ‘quiet mode’.

³`pdfcrop` requires a Perl installation under Windows, freely available from <http://www.activestate.com/Products/activeperl/index.plex>

4.6 Auxiliary processing command line options

The command line options passed to each program of the auxiliary processing can be changed with the following package options:

```
[latex-options    = ...]
[dvips-options    = ...]
[ps2pdf-options  = ...] and,
[pdfcrop-options = ...] (if applicable).
```

For the most part these will be unnecessary, although passing the correct options to `ps2pdf` can sometimes be a little obscure.⁴ For example, I used the following for generating figures in my thesis:

```
ps2pdf-options={-dPDFSETTINGS=/prepress}
```

This forces the ‘base fourteen’ fonts to be embedded within the individual figure files, without which some printers and PDF viewers have trouble with the textual labels. In fact, from v1.3 of `pstool`, this option is now the default. Note that subsequent calls to `[ps2pdf-options=...]` will override the `pstool` default; use `ps2pdf-options={}` to erase `ps2pdf`’s defaults if necessary.

At some point in the past, the behaviour of `ps2pdf` has changed under Windows. Previously, options to `ps2pdf` needed to be quoted and use `=` to assign its options. Something about this changed, and it appears the best way to set `ps2pdf` options to use the `#` character instead. Therefore, `pstool` attempts to be clever and replaces all instances of `=` within a `ps2pdf` option into `#` (under Windows only). No quotes are added. Windows users can therefore continue to use `=` to set `ps2pdf` options and allow `pstool` to make the substitution; their documents will still compile correctly on macOS or Linux platforms.

4.7 Compression of bitmap data

In the conversion using `ps2pdf`, bitmap images are stored using either lossy or lossless compression. The default behaviour for `pstool` is to force lossless compression, because we believe that to be the most commonly desired use case (you don’t want scientific graphics rendered with possible compression artifacts). This behaviour can be adjusted using one of these options:⁵

```
[bitmap=auto] : Do whatever ps2pdf does by default, which seems to be to use
               lossy compression most, if not all, of the time;
[bitmap=lossy] : Bitmap images are compressed like JPEG; this is only really
               suitable for photographs;
```

⁴The manual is here: <http://pages.cs.wisc.edu/~ghost/doc/cvs/Ps2pdf.htm>

⁵Technical details are given in section 5.5.

`[bitmap=lossless]` (*default*) : Bitmap images are compressed like PNG; this is suitable for screenshots and generated data such as a surface plot within Matlab.

These are just special cases of the `[ps2pdf-options=...]` option, but using `[bitmap=...]` is much more convenient since the `ps2pdf` options to effect this behaviour are quite verbose. Note that the `auto` and `lossy` outputs differ in quality; `lossy` is lower quality than `auto` even when the latter uses a lossy compression scheme. Adjusting the quality for these options is only possible with relatively complex Ghostscript options.

4.8 Cross-referencing

To allow graphics that relied on cross-referencing of equation numbers, bibliographic citations, and so on, `pstool` attempts to transfer data to and from the `.aux` file for each processed graphic. See Section 5.3 for more details. This feature can be disabled for compatibility or performance reasons using the `[crossref=false]` option. (Its converse, `[crossref=true]`, is the default in case you wish to set it explicitly.)

Enabling or disabling the cross-referencing feature can only be performed in the preamble of the document.

5 Miscellaneous details

5.1 Conditional preamble or setup commands

It can be necessary to use a slightly different preamble for the main document compared to the auxiliary file used to process each graphic individually. To have preamble material be directed at only one or the other, use the `\ifpdf` command (automatically loaded from the `ifpdf` package) as follows:

```
\ifpdf
  % main preamble only
\else
  % graphics preamble only
\fi
```

For example, when using `beamer` and showing navigation symbols on each slide, you want to suppress these in the `pstool`-generated graphics (else they'll show up twice!). In this case, the preamble snippet would look something like:

```
\ifpdf\else
  \setbeamertemplate{navigation symbols}{}
\fi
```

It would be possible to provide specific pstool commands or environments to do this; let me know if the `\ifpdf` approach doesn't work for you. For larger amount of preamble material that should be omitted for each graphic, the `\EndPreamble` command (see next) might also help.

5.2 The `\EndPreamble` command

The pstool package scans the beginning of the main document to insert its preamble into each graphic that is converted. This feature hasn't been well-tested and there are certain cases in which it is known to fail. (For example, if `\begin{document}` doesn't appear on a line by itself.) If you need to indicate the end of the preamble manually because this scanning has failed, place the command `\EndPreamble` where-ever you'd like the preamble in the auxiliary processing to end. This is also handy to bypass anything in the preamble that will never be required for the figures but which will slow down or otherwise conflict with the auxiliary processing.

5.3 Cross-referencing

pstool supports cross-referencing within graphics. That is, you can use `\ref` and `\cite`, etc., within `psfrag` commands. In fact, references to page numbers within an external figure should now resolve correctly; e.g., you can use `\thepage` within a `psfrag` command. (I haven't really tested, but this should allow any package that writes information to the `.aux` file to work correctly.)

The implementation to achieve this is somewhat convoluted and difficult to extend, but the user interface should work just as you would expect, mostly. The main gotcha to keep in mind is that when cross-referencing is used, the graphics will need multiple compilations to resolve all the cross-references properly. Therefore, I recommend when setting such figures up in your document to use the `\psfragfig*` command, which forces graphics compilation every time, and remove the star only when you're sure the graphic is now correct. Alternatively, don't worry about the resolving of the cross-references until the very end, and then load the package with the `[process=all]` option.

As the code for processing data through the `.aux` file can have unwanted interactions with other packages, or just be a little slower, you can disable the cross-referencing feature by loading pstool with the `[crossref=false]` package option.

5.4 A note on file paths

The pstool package tries to ensure that you can put image files in subdirectories of the main document and the auxiliary processing will still function

correctly. In order to ensure this, the external `pdflatex` compilation uses the `-output-directory` feature of `pdfTeX`. This command line option is definitely supported on all platforms from TeX Live 2008 and MiKTeX 2.7 onwards, but earlier distributions may not be supported.

One problem that `pstool` does not solve on its own is the inclusion of images that do not exist in subdirectories of the main document. For example, `\pstool{../Figures/myfig}` can not process by default because `pdfTeX` usually does not have permission to write into folders that are higher in the hierarchy than the main document. This can be worked around presently in two different ways: (although maybe only for Mac OS X and Linux)

1. Give `pdflatex` permission to write anywhere with the command:
`openout_any=a pdflatex ...`
2. Create a symbolic link in the working directory to a point higher in the path: `ln -s ../../PhD ./PhD`, for example, and then refer to the graphics through this symbolic link.

5.5 Technical details on `ps2pdf`'s bitmap options

The `[bitmap=auto]` `pstool` option does not set any `ps2pdf` options; use this if you wish to set the following `ps2pdf` options manually.

For both `[bitmap=lossless]` (default) and `[bitmap=lossy]`, the following `ps2pdf` options are set:

```
-dAutoFilterColorImages=false  
-dAutoFilterGrayImages=false
```

Then for lossless image encoding, the following options are set:

```
-dColorImageFilter=/FlateEncode  
-dGrayImageFilter=/FlateEncode
```

Instead for lossy encoding, these are the options used:

```
-dColorImageFilter=/DCTEncode  
-dGrayImageFilter=/DCTEncode
```

If there are more `ps2pdf` options that you frequently use, please let me know and it may be a good idea to add `pstool` wrappers to make them more convenient.

Part II

Implementation

6 Package information

The most recent publicly released version of pstool is available at CTAN: <http://tug.ctan.org/pkg/pstool/>. Historical and developmental versions are available at GitHub: <http://github.com/wspr/pstool/>. While general feedback via email is welcomed, specific bugs or feature requests should be reported through the issue tracker: <http://github.com/wspr/pstool/issues>.

6.1 Licence

This package is freely modifiable and distributable under the terms and conditions of the L^AT_EX Project Public Licence, version 1.3c or greater (your choice).⁶ This work consists of the files `pstool.tex` and the derived files `pstool.sty`, `pstool.ins`, and `pstool.pdf`. This work is maintained by WILL ROBERTSON.

7 Code

Note that the following code is typeset in a non-verbatim manner; indentation is controlled automatically by some hastily written macros (and will sometimes not indent as might be done manually). When in doubt, consult the source directly!

This work may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3c or (at your option) any later version. The latest version of this license is in: `<http://www.latex-project.org/lppl.txt>` This work has the LPPL maintenance status ‘maintained’. The Current Maintainer of this work is Will Robertson.

```
13 \ProvidesPackage{pstool}[2018/01/20 v1.5e Wrapper for processing PostScript/psfrag
```

TODO: convert this package into expl3 syntax (will save many lines of code).

External packages:

```
18 \RequirePackage{
19   catchfile,color,ifpdf,ifplatform,filemod,
20   graphicx,psfrag,shelless,suffix,trimspaces,xkeyval,expl3
```

⁶<http://www.latex-project.org/lppl.txt>

```
21 }  
1 }
```

Add an additional command before trimspaces.sty is updated formally:

```
24 \providecommand*{1\trim@multiple@spaces@in1}[1]{1%  
25   \let\trim@temp#1%  
26   \trim@spaces@in#1%  
27   \ifx\trim@temp#1%  
28   \else  
29     \expandafter\trim@multiple@spaces@in\expandafter#1%  
30   \fi  
31 }  
1 }
```

7.1 Allocations

```
34 \expandafter\newif\csname if@pstool@pdfcrop@\endcsname  
35 \expandafter\newif\csname if@pstool@verbose@\endcsname  
36 \expandafter\newif\csname if@pstool@crossref@\endcsname  
37 \expandafter\newif\csname if@pstool@has@written@aux\endcsname  
  
39 \newwrite\pstool@out  
40 \newread\pstool@mainfile@ior  
41 \newread\pstool@auxfile@ior
```

Macro used to store the name of the graphic's macro file:

```
44 \let\pstool@tex\@empty
```

7.2 Package options

```
48 \define@choicekey*{1pstool.sty1}{1crop1}  
49   [ \@tempa\@tempb ] {1preview, pdfcrop1 } {1%  
50   \ifcase\@tempb\relax  
51     \@pstool@pdfcrop@false  
52   \or  
53     \@pstool@pdfcrop@true  
54   \or  
55   \fi  
56 }  
1 }
```

```

58 \define@choicekey*{pstool.sty}{process_1}
59     [ \@tempa\pstool@process@choice]{_1all,none,auto_1}{}
60 \ExecuteOptionsX{process=auto_1}

62 \define@choicekey*{pstool.sty}{mode_1}
63     [ \@tempa\@tempb]{_1errorstop,nonstop,batch_1}{_1%
64     \ifnum\@tempb=2\relax
65     \@pstool@verbose@false
66     \else
67     \@pstool@verbose@true
68     \fi
69     \edef\pstool@mode{2\@tempa mode_2}%
70 }
71 \ExecuteOptionsX{mode=batch_1}

73 \DeclareOptionX{cleanup_1}{_1%
74     \edef\pstool@rm@files{2\zap@space #1 \@empty_2}%
75     \if@pstool@crossref@
76     \@for\@ii:=\pstool@rm@files\do{2%
77     \edef\@tempa{3\@ii_3}%
78     \def\@tempb{3.aux_3}%
79     \ifx\@tempa\@tempb
80     \PackageWarning{3pstool_3}{3^^J\space\space%
81     You have requested that ".aux" files be deleted.^^J\space\space
82     Cross-referencing within pstool graphics therefore disabled.^^J%
83     This warning occurred_3}
84     \fi
85 }_2}%
86 \fi
87 }_1}
88 \ExecuteOptionsX{cleanup={2.tex,.dvi,.ps,.pdf,.log_2}_1}

90 \define@choicekey*{pstool.sty}{crossref_1}[\@tempa\@tempb]{_1false,true_1}{_1%
91     \ifcase\@tempb\relax
92     \@pstool@crossref@false
93     \or
94     \@pstool@crossref@true
95     \or
96     \fi
97 }_1}
98 \@onlypreamble\@pstool@crossref@true

```

```

99 \onlypreamble\@pstool@crossref@false
100 \ExecuteOptionsX{1crossref=true1}

102 \DeclareOptionX{1suffix1}{1\def\pstool@suffix{2#12}1}
103 \ExecuteOptionsX{1suffix={2-pstool2}1}

```

There is an implicit \space after the bitmap options.

```

106 \define@choicekey*{1pstool.sty1}{1bitmap1}
107   [ \@tempa\@tempb ] {1auto,lossless,lossy1 } {1%
108   \ifcase\@tempb
109     \let\pstool@bitmap@opts\@empty
110   \or
111     \def\pstool@bitmap@opts{2%
112       -dAutoFilterColorImages=false
113       -dAutoFilterGrayImages=false
114       -dColorImageFilter=/FlateEncode
115       -dGrayImageFilter=/FlateEncode % space
116     }2}
117   \or
118     \def\pstool@bitmap@opts{2%
119       -dAutoFilterColorImages=false
120       -dAutoFilterGrayImages=false
121       -dColorImageFilter=/DCTEncode
122       -dGrayImageFilter=/DCTEncode % space
123     }2}
124   \fi
125 }1}
126 \ExecuteOptionsX{1bitmap=lossless1}

128 \DeclareOptionX{1latex-options1}{1\def\pstool@latex@opts{2#12}1}
129 \DeclareOptionX{1dvips-options1}{1\def\pstool@dvips@opts{2#12}1}
130 \DeclareOptionX{1ps2pdf-options1}{1\def\pstool@pspdf@opts{2#12}1}
131 \DeclareOptionX{1pdfcrop-options1}{1\def\pstool@pdfcrop@opts{2#12}1}

133 \ExecuteOptionsX{1
134   latex-options={},
135   dvips-options={},
136   ps2pdf-options={2-dPDFSETTINGS=/prepress2},
137   pdfcrop-options={}
138 }1}

```

```

140 \DeclareOptionX{macro-file}_{1}%
141   \IfFileExists{#1}_{2}
142     {_2\def\pstool@macrofile{#1}_{3}}
143     {_2%
144       \let\pstool@macrofile\@empty
145       \PackageError{pstool}_{_3^^J\space\space%
146         No file ‘#1’ found for "macro-file" package option.^^J
147         This warning occurred}_{3}
148     }
149 }

```

Default:

```

152 \IfFileExists{\jobname-pstool.tex}
153   {_1\edef\pstool@macrofile{jobname-pstool.tex}_{2}}
154   {_1\let\pstool@macrofile\@empty}_{1}

157 \ifpdf
158   \ifshellescape\else
159     \ExecuteOptionsX{process=none}_{1}
160     \PackageWarning{pstool}_{_1^^J\space\space%
161       Package option [process=none] activated^^J\space\space
162       because -shell-escape is not enabled.^^J%
163       This warning occurred}_{1}
164   \fi
165 \fi

167 \ProcessOptionsX

```

A command to set pstool options after the package is loaded.

```

170 \newcommand\pstoolsetup{1}%
171   \setkeys{pstool.sty}_{2}%
172 }

```

8 Macros

Used to echo information to the console output. Can't use \typeout because it's asynchronous with any \immediate\write18 processes (for some reason).

```

178 \def\pstool@echo#1{1%
179   \if@pstool@verbose@
180     \pstool@echo@verbose{2#12}%
181   \fi
182 1}

184 \def\pstool@echo@verbose#1{1%
185   \ShellEscape{2echo "#1"2}%
186 1}

188 \let\pstool@includegraphics\includegraphics

```

Command line abstractions between platforms:

```

191 \edef\pstool@cmdsep{1\ifwindows\string&\else\string;\fi\space1}
192 \edef\pstool@rm@cmd{1\ifwindows del \else rm - \fi1}
193 \edef\pstool@cp@cmd{1\ifwindows copy \else cp - \fi1}

```

Delete a file if it exists:

#1: path

#2: filename

```

198 \newcommand\pstool@rm[2]{1%
199   \IfFileExists{2#1#22}{2%
200     \ShellEscape{3%
201       cd "#1"\pstool@cmdsep\pstool@rm@cmd "#2"
202     3}%
203   2}{}%
204 1}

```

Copy a file if it exists:

#1: path

#2: filename

#3: new filename

```

210 \newcommand\pstool@cp[3]{1%
211   \IfFileExists{2#1#22}{2%
212     \ShellEscape{3%
213       cd "#1"\pstool@cmdsep\pstool@cp@cmd "#2" "#3"
214     3}%
215   2}{}%
216 1}

```

Generic function to execute a command on the shell and pass its exit status back into L^AT_EX. Any number of `\pstool@exe` statements can be made consecutively followed by `\pstool@endprocess`, which also takes an argument. If *any* of the shell calls failed, then the execution immediately skips to the end and expands `\pstool@error` instead of the argument to `\pstool@endprocess`.

#1: 'name' of process #2: relative path where to execute the command #3: the command itself

```

222 \newcommand\pstool@exe[3]{_1%
223   \pstool@echo{_^J=== pstool: #1 ===_2}%
224   \pstool@shellexecute{_2#2}_{_3#3}_2}%
225   \pstool@retrievestatus{_2#2}_2}%
226   \ifnum\pstool@status > \z@
227     \PackageWarning{_2pstool_2}{_2%
228       Execution failed during process:_^J\space\space
229       #3_^JThis warning occurred%
230     }_2}%
231   \expandafter\pstool@abort
232 \fi
233 }_1}

```

Edit this definition to print something else when graphic processing fails.

```

236 \def\pstool@error{_1%
237   \fbox{_2%
238     \parbox{_30.8\linewidth_3}{_3%
239       \color{_4red_4}\centering\ttfamily\scshape\small
240       An error ocured processing graphic:\\
241       \upshape‘%
242       \detokenize\expandafter{_4\pstool@path_4}_4}%
243       \detokenize\expandafter{_4\pstool@filestub_4}.eps%
244       ’\\bigskip
245       \tiny
246       Check the log file for compilation errors:\\
247       ‘%
248       \detokenize\expandafter{_4\pstool@path_4}_4}%
249       \detokenize\expandafter{_4\pstool@filestub_4}-pstool.log%
250     }_3}%
251   }_2}%
252 }_1}
253
255 \def\pstool@abort#1\pstool@endprocess{_1\pstool@error\@gobble_1}

```



```
256 \let\pstool@endprocess\@firstofone
```

It is necessary while executing commands on the shell to write the exit status to a temporary file to test for failures in processing. (If all versions of pdf_latex supported input pipes, things might be different.)

```
259 \def\pstool@shellexecute#1#2{1%
260   \ShellEscape{2%
261     cd "#1" \pstool@cmdsep
262     #2 \pstool@cmdsep
263     \ifwindows
264       call echo
265       \string^ \@percentchar ERRORLEVEL\string^ \@percentchar
266     \else
267       echo \detokenize{3$?}
268     \fi
269   > \pstool@statusfile2}%
```

That's the execution; now we need to flush the write buffer to the status file. This ensures the file is written to disk properly (allowing it to be read by `\CatchFileEdef`). Not necessary on Windows, whose file writing is evidently more crude/immediate.

```
271   \ifwindows\else
272     \ShellEscape{2%
273       touch #1\pstool@statusfile2}%
274   \fi
275 1}
276 \def\pstool@statusfile{1pstool-statusfile.txt1}
```

Read the exit status from the temporary file and delete it. `#1` is the path Status is recorded in `\pstool@status`.

```
281 \def\pstool@retrievestatus#1{1%
282   \CatchFileEdef{2\pstool@status2}{2#1\pstool@statusfile2}{2}%
283   \pstool@rm{2#12}{2\pstool@statusfile2}%
284   \ifx\pstool@status\pstool@statusfail
285     \PackageWarning{2pstool2}{2%
286       Status of process unable to be determined:^^J #1^^J%
287       Trying to proceed... 2}%
288     \def\pstool@status{202}%
289   \fi
290 1}
291 \def\pstool@statusfail{1\par 1}% what results when TEX reads an empty file
```

Grab filename and filepath. Always need a relative path to a filename even if it's in the same directory.

```

294 \def\pstool@getpaths#1{1%
295   \filename@parse{2#1}2%
296   \ifx\filename@area\@empty
297     \def\pstool@path{2./2}%
298   \else
299     \let\pstool@path\filename@area
300   \fi
301   \let\pstool@filestub\filename@base
302 1}

```

The filename of the figure stripped of its path, if any: (analogous to standard `\jobname`)

```

306 \def\pstool@jobname{1\pstool@filestub\pstool@suffix1}

```

9 Command parsing

User input is `\pstool` (with optional `*` or `!` suffix) which turns into one of the following three macros depending on the mode.

```

312 \newcommand\pstool@alwaysprocess[3] [] {1%
313   \pstool@getpaths{2#2}2%
314   \pstool@process{2#12}{2#32}%
315 1}

317 \ifpdf
318   \newcommand\pstool@neverprocess[3] [] {1%
319     \pstool@includegraphics{2#2}2%
320   1}
321 \else
322   \newcommand\pstool@neverprocess[3] [] {1%
323     \begingroup
324     \setkeys*{2pstool.sty2}{2#12}%
325     #3%
326     \expandafter\pstool@includegraphics\expandafter[\XKV@rm]{2#2}2%
327   \endgroup
328 1}

```

```
329 \fi
```

Process the figure when:

- the PDF file doesn't exist, or
- the EPS is newer than the PDF, or
- the TeX file is new than the PDF.

```
335 \ExplSyntaxOn
336 \newcommand\pstool@maybeprocess[3] []
337   {
338     \pstool_if_should_process:nTF {#2}
339     { \pstool@process{#1}{#3} }
340     { \pstool@includegraphics{#2} }
341   }

343 \prg_set_conditional:Nnn \pstool_if_should_process:n {TF}
344   {
345     \pstool@getpaths{#1}

347     \file_if_exist:nF {#1.pdf}
348     { \use_i_delimit_by_q_stop:nw \prg_return_true: }

350     \filemodCmp { \pstool@path\pstool@filestub.eps }
351               { \pstool@path\pstool@filestub.pdf }
352     { \use_i_delimit_by_q_stop:nw \prg_return_true: } {}

354 \exp_args:Nx \clist_map_inline:nn { \pstool@macrofile , \pstool@tex }
355 % empty entries are ignored in clist mappings, so no need to filter here
356   {
357     \filemodCmp {##1} { \pstool@path\pstool@filestub.pdf }
358     {
359       \clist_map_break:n { \use_i_delimit_by_q_stop:nw \prg_return_true: }
360     }
361   }

362   {

364     \filemodCmp { \pstool@path\pstool@filestub.tex }
365               { \pstool@path\pstool@filestub.pdf }
366     { \use_i_delimit_by_q_stop:nw \prg_return_true: } {}

368     \use_i_delimit_by_q_stop:nw \prg_return_false:
369     \q_stop
```

```

370   }
371 \ExplSyntaxOff

```

10 User commands

Finally, define `\pstool` as appropriate for the mode: (all, none, auto, respectively)

```

375 \ifpdf
376   \newcommand\pstool{1%
377     \ifcase\pstool@process@choice\relax
378     \expandafter \pstool@alwaysprocess \or
379     \expandafter \pstool@neverprocess \or
380     \expandafter \pstool@maybeprocess
381   \fi
382 }
383 \WithSuffix\def\pstool!{1%
384   \ifcase\pstool@process@choice\relax
385   \expandafter \pstool@alwaysprocess \or
386   \expandafter \pstool@neverprocess \or
387   \expandafter \pstool@neverprocess
388 \fi
389 }
390 \WithSuffix\def\pstool*{1%
391   \ifcase\pstool@process@choice\relax
392   \expandafter \pstool@alwaysprocess \or
393   \expandafter \pstool@neverprocess \or
394   \expandafter \pstool@alwaysprocess
395 \fi
396 }
397 \else
398   \let\pstool\pstool@neverprocess
399   \WithSuffix\def\pstool!{1\pstool@neverprocess1}
400   \WithSuffix\def\pstool*{1\pstool@neverprocess1}
401 \fi

```

11 The figure processing

And this is the main macro.

```
406 \newcommand\pstool@process[2]{1%
407   \begingroup
408   \setkeys*{2pstool.sty}{2#12}%
409   \pstool@echo@verbose{2%
410     ^^J^^J=== pstool: begin processing ===2}%
411   \pstool@write@processfile{2#12}
412     {2\pstool@path\pstool@filestub2}{2#22}%
413   \pstool@exe{2auxiliary process: \pstool@filestub\space2}
414     {2./2}{2latex
415     -shell-escape
416     -output-format=dvi
417     -output-directory="\pstool@path"
418     -interaction=\pstool@mode\space
419     \pstool@latex@opts\space
420     "\pstool@jobname.tex"2}%
```

Execute dvips in quiet mode if latex is not run in (non/error)stop mode:

```
422   \pstool@exe{2dvips2}{2\pstool@path2}{2%
423     dvips \if@pstool@verbose@else -q \fi -Ppdf
424     \pstool@dvips@opts\space "\pstool@jobname.dvi"2}%
```

Pre-process ps2pdf options for Windows (sigh):

```
426   \pstool@pspdf@opts@preprocess \pstool@bitmap@opts
427   \pstool@pspdf@opts@preprocess \pstool@pspdf@opts
```

Generate the PDF:

```
429   \if@pstool@pdfcrop@
430     \pstool@exe{2ps2pdf2}{2\pstool@path2}{2%
431       ps2pdf \pstool@bitmap@opts \pstool@pspdf@opts \space
432       "\pstool@jobname.ps" "\pstool@jobname.pdf"2}%
433     \pstool@exe{2pdfcrop2}{2\pstool@path2}{2%
434       pdfcrop \pstool@pdfcrop@opts\space
435       "\pstool@jobname.pdf" "\pstool@filestub.pdf"2}%
436   \else
437     \pstool@exe{2ps2pdf2}{2\pstool@path2}{2%
438       ps2pdf \pstool@bitmap@opts \pstool@pspdf@opts \space
439       "\pstool@jobname.ps" "\pstool@filestub.pdf"2}%
440   \fi
```

Finish up: (implies success!)

```
442 \pstool@endprocess{2%  
443 \pstool@includegraphics{3\pstool@path\pstool@filestub3}%
```

Emulate \include (sort of) and have the main document load the auxiliary aux file, in a manner of speaking:

```
445 \if@pstool@crossref@  
446 \pstool@write@aux  
447 \fi  
448 \pstool@cleanup  
449 2}%  
450 \pstool@echo@verbose{2^^J=== pstool: end processing ===^^J2}%  
451 \endgroup  
452 1}  
  
454 \newcommand\pstool@write@aux{1%  
455 \endlinechar=-1\relax  
456 \@tempswatrue  
457 \@pstool@has@written@auxfalse  
458 \in@false  
459 \openin \pstool@auxfile@ior "\pstool@path\pstool@jobname.aux"\relax  
460 \@whilesw \if@tempswa \fi {2%  
461 \readline \pstool@auxfile@ior to \@tempa  
462 \ifeof \pstool@auxfile@ior  
463 \@tempswafalse  
464 \else  
465 \edef\@tempb{3\detokenize\expandafter{4\pstool@auxmarker@text/4}3}%  
466 \ifx\@tempa\@tempb  
467 \@tempswafalse  
468 \else  
469 \if@pstool@has@written@aux  
470 \immediate\write\@mainaux{3\unexpanded\expandafter{4\@tempa4}3}%  
471 \fi  
472 \edef\@tempb{3\detokenize\expandafter{4\pstool@auxmarker@text*4}3}%  
473 \ifx\@tempa\@tempb  
474 \@pstool@has@written@auxtrue  
475 \fi  
476 \fi  
477 \fi  
478 2}%  
479 \closein \pstool@auxfile@ior  
480 1}
```

```

482 \ExplSyntaxOn
483 \cs_new:Npn \pstool@pspdf@opts@preprocess #1
484   {1
485   \ifwindows
486     \exp_args:NNnx \tl_replace_all:Nnn #1 {2=2} {2 \cs_to_str:N \# 2}
487   \fi
488   }1
489 \ExplSyntaxOff

```

For what's coming next.

```

492 \edef\@begindocument@str{1\detokenize\expandafter{2\string\begin{3document3}2}1}
493 \edef\@endpreamble@str{1\string\EndPreamble1}
494 \def\in@first#1#2{1\in@{2NEVEROCCUR!#12}{2NEVEROCCUR!#22}1}

```

We need to cache the aux file, since it is cleared for writing after \begindocument.

```

497 \ifpdf
498   \pstool@rm{1\jobname.oldaux1}
499   \pstool@cp{1\jobname.aux1}{1\jobname.oldaux1}
500   \AtEndDocument{1\pstool@rm{2\jobname.oldaux2}1}
501 \fi

503 \edef\pstool@auxmarker#1{1\string\@percentchar\space <#1PSTOOLLABELS>1}
504 \edef\pstool@auxmarker@text#1{1\@percentchar <#1PSTOOLLABELS>1}

```

The file that is written for processing is set up to read the preamble of the original document and set the graphic on an empty page (cropping to size is done either here with preview or later with pdfcrop).

```

507 \def\pstool@write@processfile#1#2#3{1%
508   \immediate\openout\pstool@out #2\pstool@suffix.tex\relax

```

Put down a label so we can pass through the current page number:

```

510 \if@pstool@crossref@
511   \edef\pstool@label{2pstool-\pstool@path\pstool@filestub2}%
512   \protected@write\@auxout{1%
513     {2\string\newlabel{3\pstool@label3}{3{4\@currentlabel4}4\the\c@page4}3}2}%

```

And copy the main file's bbl file too: (necessary only for biblatex but do it always)

```

515   \pstool@rm{2\pstool@path2}{2\pstool@jobname.bbl2}%

```

```

516     \pstool@cp{ }{ } \jobname.bbl }{ } \pstool@path \pstool@jobname.bbl }%
517     \fi

```

Scan the main document line by line; print preamble into auxiliary file until the document begins or \EndPreamble is found:

```

519     \endlinechar=-1\relax
520     \def\@tempa{ \pdfoutput=0\relax }%
521     \in@false
522     \openin \pstool@mainfile@ior " \jobname " \relax
523     \@whilesw \unless\ifin@ \fi { %
524         \immediate\write \pstool@out{ \unexpanded\expandafter{ \@tempa } }%
525         \readline \pstool@mainfile@ior to \@tempa
526         \let \@tempc \@tempa
527         \trim@multiple@spaces@in \@tempa
528         \expandafter\expandafter\expandafter\in@first
529         \expandafter\expandafter\expandafter{ %
530         \expandafter\@begindocument@str
531         \expandafter } %
532         \expandafter{ \@tempa }%
533         \unless\ifin@
534             \expandafter\expandafter\expandafter\in@first
535             \expandafter\expandafter\expandafter{ %
536             \expandafter\@endpreamble@str
537             \expandafter } %
538             \expandafter{ \@tempa }%
539         \fi
540     } %
541     \closein \pstool@mainfile@ior

```

Now the preamble of the process file:

```

543     \immediate\write \pstool@out{ %
544     \if@pstool@pdfcrop@ \else
545         \noexpand\usepackage [active,tightpage] { preview } ^^J %
546     \fi
547     \unexpanded{ %
548         \pagestyle{ empty } ^^J ^^J % remove the page number
549     } %
550     \noexpand\makeatletter ^^J %

```

Sort out the page numbering here. Force the pagestyle locally to output an integer so it can be written to the external file inside a \setcounter command.

```

553     \if@pstool@crossref@
554     \expandafter\ifx\csname r@\pstool@label\endcsname\relax\else

```



```

555     \def\noexpand\thepage{3\unexpanded\expandafter{4\thepage4}3}^^J%
556     \noexpand\setcounter{3page3}{3%
557         \expandafter\expandafter\expandafter
558         \@secondoftwo\csname r@\pstool@label\endcsname
559     }3}^^J%
560     \fi
561     \fi

```

And the document body to place the graphic on a page of its own:

```

563     \if@pstool@crossref@
564     \noexpand\@input{3\jobname.oldaux3}^^J%
565     \fi
566     \noexpand\makeatother^^J^^J%
567     \noexpand\begin{3document3}^^J%
568     \if@pstool@crossref@
569     \noexpand\makeatletter^^J%
570     \unexpanded{3\immediate\write\@mainaux3}{3\pstool@auxmarker*3}^^J%
571     \noexpand\makeatother^^J^^J%
572     \fi
573     \unexpanded{3%
574         \centering\null\vfill^^J%
575     }3%
576     ^^J%
577     \if@pstool@pdfcrop@else
578     \noexpand\begin{3preview3}^^J%
579     \fi
580     \unexpanded{3#3^^J3}
581     \noexpand\includegraphics
582         [\unexpanded\expandafter{3\XKV@rm3}]
583         {3\pstool@filestub3}^^J%
584     \if@pstool@pdfcrop@else
585     \noexpand\end{3preview3}^^J%
586     \fi
587     ^^J%
588     \if@pstool@crossref@
589     \unexpanded{3\vfill^^J^^J\makeatletter^^J\immediate\write\@mainaux3}{3\pstool@aux
590     \unexpanded{3\makeatother^^J3}^^J%
591     \fi
592     \unexpanded{3\end{4document4}3}^^J%
593     }2%
594     \immediate\closeout\pstool@out
595     }1

```

```

597 \def\pstool@cleanup{1%
598   \for\@ii:=\pstool@rm@files\do{2%
599     \pstool@rm{3\pstool@path3}{3\pstool@jobname\@ii3}%
600   }2%
601 }1}

603 \providecommand\EndPreamble{}

```

12 User commands

These all support the suffixes * and !, so each user command is defined as a wrapper to \pstool.

For EPS figures with psfrag:

```

609 \newcommand\psfragfig[2] [] {1\pstool@psfragfig{2#12}{2#22}{1}
610 \WithSuffix\newcommand\psfragfig*[2] [] {1%
611   \pstool@psfragfig{2#12}{2#22}{2*2}%
612 }1}
613 \WithSuffix\newcommand\psfragfig![2] [] {1%
614   \pstool@psfragfig{2#12}{2#22}{2!2}%
615 }1}

```

Parse optional input definitions:

```

618 \newcommand\pstool@psfragfig[3] {1%
619   \@ifnextchar\bgroup{2%
620     \pstool@psfragfig{3#13}{3#23}{3#33}%
621   }2{2%
622     \pstool@psfragfig{3#13}{3#23}{3#33}{1}%
623   }2%
624 }1}

```

Search for both ‘filename’ and ‘filename’-psfrag inputs.

- #1: possible graphicx options
- #2: graphic name (possibly with path)
- #3: \pstool suffix (i.e., ! or * or ‘empty’)
- #4: possible psfrag (or other) macros

```

631 \newcommand\pstool@psfragfig[4] {1%
632   % Find the .eps file to use.

```

```

633 \IfFileExists{#2-psfrag.eps}{%
634 \edef\pstool@eps{#2-psfrag}%
635 \IfFileExists{#2.eps}{%
636 \PackageWarning{pstool}{%
637 Graphic "#2.eps" exists but "#2-psfrag.eps" is being used%
638 }%
639 }}%
640 }{%
641 \IfFileExists{#2.eps}{%
642 \edef\pstool@eps{#2}%
643 }{%
644 \PackageError{pstool}{%
645 No graphic "#2.eps" or "#2-psfrag.eps" found%
646 }{%
647 Check the path and whether the file exists.%
648 }%
649 }}%
650 }%
651 % Find the .tex file to use.
652 \IfFileExists{#2-psfrag.tex}{%
653 \edef\pstool@tex{#2-psfrag.tex}%
654 \IfFileExists{#2.tex}{%
655 \PackageWarning{pstool}{%
656 File "#2.tex" exists that may contain macros
657 for "\pstool@eps.eps"
658 But file "#2-psfrag.tex" is being used instead.%
659 }%
660 }}%
661 }{%
662 \IfFileExists{#2.tex}{%
663 \edef\pstool@tex{#2.tex}%
664 }{%
665 \PackageWarning{pstool}{%
666 No file "#2.tex" or "#2-psfrag.tex" can be found
667 that may contain macros for "\pstool@eps.eps"%
668 }%
669 }}%
670 }%
671 % Perform the actual processing step, skipping it entirely if an EPS file hasn't been found.
672 % (In which case an error would have been called above; this is to clean up nicely in scrollmode, for e
673 \ifx\pstool@eps\undefined\else

```

```

674 \edef\@tempa{2%
675 \unexpanded{3\pstool#3[#1]3}{3\pstool@eps3}{3%
676 \ifx\pstool@macrofile\@empty\else
677 \unexpanded{4\csname @input\endcsname4}{4\pstool@macrofile4}%
678 \fi
679 \ifx\pstool@tex\@empty\else
680 \unexpanded{4\csname @input\endcsname4}{4\pstool@tex4}%
681 \fi
682 \unexpanded{4#44}%
683 }%
684 }2\@tempa
685 \fi
686 }1

```

—The End—